

---

**Product specifications for model 1201**


---

**Product Specifications**

<b>sensor type</b>	piston
<b>functions</b>	gauge, gauge/switch, switch
<b>min. range</b>	0-5 psid
<b>max. range</b>	0-150 psid
<b>max. line pressure</b>	3000 psig
<b>min. burst pressure</b>	10500 psig
<b>standard maximum temperature</b>	gauge: 200°F standard, 150°F (plastic lens) gauge/switch: 176°F standard, 150°F (plastic lens) switch: 176°F standard
<b>high temperature construction</b>	gauge: 450°F (SS), 400°F (naval brass), 300°F (alum) gauge/switch, switch: N/A
<b>minimum temperature*</b>	<i>*Consult factory for low-temperature applications.</i>
<b>calibration accuracy**</b>	±2% of full scale ascending after rap at room temperature <i>**Calibration accuracy is affected by temperature, and also by liquid-filling and follower-pointer options.</i>
<b>repeatability</b>	±2% of full scale
<b>switches</b>	1 or 2 external hermetically sealed reed switches
<b>switch adjustability</b>	upper 80% of full scale ascending (70% for B & C form switches in SST)
<b>switch dead band</b>	5-20% full scale
<b>certification</b>	CSA (File 043810) <i>*Consult factory for CE equivalent.</i>

**Standard configuration options**

<b>configuration</b>	<b>unless otherwise specified</b>	<b>standard options available</b>
<b>porting size</b>	1/4" NPT	1/8" NPT, 1/2" NPT, AND and MS ports
<b>porting orientation</b>	(must be specified)	gauge: in-line, back, or bottom gauge/switch: in-line, back, or bottom switch: in-line porting only
<b>direction of pressure</b>	left to right	right to left (reverse porting)
<b>calibration medium</b>	all units with EPDM seals: water all others: alum or SS: hydraulic oil brass or PVC: water	N/A
<b>switches</b>	(must be specified)	-A SPST N/O (120VAC,0.7A,70VA;200VDC,1.0A,50W) -B SPST N/C (120VAC,0.25A,5VA;175VDC,0.25A,5W) -C SPDT (120VAC,0.25A,5VA;175VDC,0.25A,5W)
<b>switch setting</b>	set at top of range ascending	other set points within adjustability ascending or descending
<b>primary wetted parts</b>	(must be specified)	aluminum, 316SS, naval brass, PVC
<b>secondary wetted parts</b>	range spring: 302SS magnet: ceramic piston seal: Teflon	Teflon-coated spring and magnet
<b>static seals</b>	buna-N, except Viton for high temp.	Viton, Teflon, neoprene, EPDM, fluorosilicone
<b>lens</b>	glass	plastic
<b>dial sizes</b>	(must be specified)	2.5", 3.5", 4.5", 6"
<b>dial case styles</b>	(must be specified)	"B" Basic Case (c-clamp available on all but 2.5") "F" Flanged Case (w/holes for panel mounting)
<b>starting mark on dial</b>	approximately 10% of full scale	N/A